

## Factory Stain Color Chart:



072 Butternut




077 Cedar



078 Natural



005 Natural Oak



009 Dark Oak



045 Mahogany



089 Redwood



085 Teak

**Sikkens Cetol SRD** is a translucent exterior satin finish stain specially formulated to provide a water repellent finish for many demanding areas of the home. Cetol SRD is an easy to use oil based effective coating for all outdoor wooden surfaces. It uses finely ground iron oxide pigments creating a rich, natural color and offers a unique protective layer against rain, snow and UV rays.

### Recommended Uses

Cetol SRD is for application to areas normally troublesome to coat with film-forming products. These application areas include roofs, wall shakes, shingles and decks. One coat application. Refer to Sikkens Proluxe application guide for details.

### Cleaning

It is recommended that the deck be cleaned with a deck cleaner. If deck is cedar deck it is recommended that the deck be brightened to neutralize the tannin oils. We recommend the Woodrich deck kit.

### Brushes

A natural china bristle brush Bravo Stainer is recommended with Sikkens Proluxe SRD stain.

### Clean-up

Paint thinner or mineral spirits

### Type

Transparent

### Coverage

- On rough and weathered surfaces, 150-250 sq. ft./gallon
- On smooth surfaces or hardwoods, 300-400 sq. ft./gallon
- Actual coverage may vary depending on the type, age and texture of the wood and application method.

### Sheen

Satin

### Description

One Coat Non-Film Forming Transparent Wood Stain.

### Dry Time

(At 68° F (20° C) and 65% relative humidity)

- Dries to touch in 2 to 4 hours.
- Dry enough to walk on in 24 hours and to place furniture back on deck.

### Usage

Siding, Railings, Decks, Siding Shakes & Shingles, Fences, Boat Docks, Outdoor Furnitures, Logs.

### Technology

Alkyd Emulsion

### Other Uses

Exterior mainly used on decks and fences.

### Sikkens Proluxe Cetol SRD features

- Easy, One-Coat Application – Can be brushed or sprayed with a pump sprayer.
- Translucent Iron Oxide Pigments – Excellent UV protection and wood grain clarity.
- Good for Decks and Siding – Multi-use product for a variety of applications.
- Highly micro-porous for areas subjected to high moisture.

### Sikkens Proluxe SRD

Can be used on Pressure treated pine or cedar lumber.

### Exotic Hardwoods

Can be use on Ipe, mahogany, iron wood, tiger wood and teak woods.



**SternbergLighting**

ESTABLISHED 1923 / EMPLOYEE OWNED

800-621-3376  
555 Lawrence Ave., Roselle, IL 60172  
info@sternberglighting.com  
www.sternberglighting.com