

6600 MORRISTOWN SERIES

SPECIFICATIONS

GENERAL

The ___ ft tall* decorative post shall be aluminum, one-piece construction. The 14" octagonal cast aluminum tapered fluted base shall be constructed with a ___ inch diameter aluminum shaft. The model shall be Sternberg Lighting #6600 or #6600R for candy cane poles. The pole shall be U.L. or E.T.L. listed in U.S. and Canada.

CONSTRUCTION

The base shall be octagonal with a twelve flute upper section which tapers to a curved shaft transition. It shall be made of heavy wall, 356 alloy cast aluminum. It shall have a 3/4" thick floor cast as an integral part of the base. The shaft shall be circumferentially welded to the base.

___ The **smooth tapered shaft** shall be made of ASTM 6063 extruded aluminum and tempered to a T6 condition.


___ The **smooth straight shaft** shall be made of ASTM 6063 extruded aluminum and tempered to a T6 condition.

___ The **straight fluted shaft** shall be made of ASTM 6061 extruded aluminum and tempered to a T6 condition. It shall have a decorative fluted 3" O.D. tenon.

INSTALLATION

Four 3/4" diameter, hot-dipped galvanized "L" type anchor bolts shall be provided with the post for anchorage. A door shall be provided for wiring and anchor bolt access. It shall be secured with tamper proof, stainless steel hardware. Post will be provided with a grounding stud mounted on the base floor opposite the access door.

Indicate the type of shaft needed (above)



**See installation template for exact door position. Bolt circle dimensions may change on taller poles.

| Cast Aluminum-Extruded Poles | | 14" Diameter Base x 36" High | |
|--|--|---|---|
| <p>4" - 3" OD 66 __ ' T4 08' 10' 12' 14'</p> <p>SMOOTH TAPERED SHAFT</p> <p>† SMOOTH STRAIGHT SHAFT AVAILABLE SPECIFY AS: 4" OD 66 __ ' P4</p> | <p>5" - 3" OD 66 __ ' T5 08' 10' 12' 14' 16'</p> <p>SMOOTH TAPERED SHAFT</p> <p>† SMOOTH STRAIGHT SHAFT AVAILABLE SPECIFY AS: 5" OD 66 __ ' P5</p> | <p>4" OD 66 __ ' FP4 08' 10' 12' 14'</p> <p>† STRAIGHT FLUTED SHAFT</p> | <p>5" OD 66 __ ' FP5 08' 10' 12' 14' 16'</p> <p>† STRAIGHT FLUTED SHAFT</p> |

*For candy cane poles insert ___ AG ft (feet - above grade height). See diagram on reverse side.

† Tenon not supplied if fixture or arm slips shaft O.D.

6600 MORRISTOWN SERIES

POSTS / OPTIONS / POST CAPS

BUILDING A PART NUMBER

Straight Poles


| MODEL / HEIGHT / SHAFT | POST CAP CENTER | OPTIONS | FINISH |
|------------------------|-----------------|---------|--------|
| 66 12 FP4 | BCC | FH | BK |

Candy Cane Poles

| MODEL / HEIGHT / SHAFT | HEIGHT ABOVE GRADE | OPTIONS | FINISH |
|------------------------|--------------------|---------|--------|
| 66 00 RT4 | 12 AG | | BK |

Part Number Selections

| MODEL | HEIGHT | SHAFT |
|-------|---|--|
| • 66 | • 08' • 10' • 12' • 14' • 16' | • T4: 4"-3" Tapered Smooth* • T5: 5"-3" Tapered Smooth • P4: 4" Straight Smooth • P5: 5" Straight Smooth • FP4: 4" Straight Fluted* • FP5: 5" Straight Fluted |



* Maximum recommended height 14'

OPTIONS AVAILABLE

- GFI
- GFB
- FH
- SBA
- DBA
- SBAR
- DSPA
- DHPA
- PA478
- PCD
- SH
- SB
- WHK
- DB Direct Burial
- HB Helix Burial

Part Number Selections

| MODEL | HEIGHT | SHAFT | ABOVE GRADE |
|-------|--------|--|--|
| • 66 | • 00 | • RT4: 4"-3" Tapered Smooth • RT5: 5"-3" Tapered Smooth • RP4: 4" Straight Smooth • RP5: 5" Straight Smooth • RFP4: 4" Straight Fluted • RFP5: 5" Straight Fluted | • 08' AG • 10' AG • 12' AG • 14' AG • 16' AG |

- #### POST CENTER CAP
- (If Required)
- BCC
 - FCC
 - SCC
 - TFCC
 - SSCC

STANDARD FINISHES*

- BKT Black Textured
 - WHT White Textured
 - PGT Park Green Textured
 - ABZT Architectural Medium Bronze Textured
 - DBT Dark Bronze Textured
- * Smooth Finishes are available upon request



CUSTOM FINISHES

- OI Old Iron

- RT Rust
- WBR Weathered Brown
- CD Cedar
- WBK Weathered Black
- TT Two Tone














STERNBERG SELECT FINISHES

- VG Verde Green
- SI Swedish Iron
- OWGT Old World Gray Textured



OPTIONS AVAILABLE

See Accessories Section for more options and information

| | | |
|---|---|--|
|  <p>GFI - Ground Fault Interrupter mounts in the pole</p>  <p>GFB - Ground Fault Breaker <i>inside</i> base</p>  <p>FH - Flag Pole Holder mounts on the pole</p>  <p>SBA - Single Banner Arm mounts on the pole</p>  <p>DBA - Double Banner Arms mount on same side of the pole</p> |  <p>SBAR - Single Banner Arm and Ring</p>  <p>DSPA - Double Stepped Planter Arms mount on either side</p>  <p>DHPA - Double Hooked Planter Arms mount on either side</p>  <p>PA478 - Decorative Planter Arms with planter rings</p> |  <p>PCD - Photo Control mounts on door on pole</p>  <p>SH - Speaker Hub for mounting speaker, floodlight or signal</p>  <p>SB - Sign Bracket mounts on pole to hold signs</p>  <p>WHK - Wreath Hook mounts on pole to hold decorations</p> |
|---|---|--|

POST CENTER CAPS (If Required)

